

Technical Data Sheet



W V C O

Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,
innovation, and integrity

EASTERN DIVISION

6662 Marbut Road
Lithonia GA 30058
Tel. 888.878.9826

WESTERN DIVISION

660 McKinley Street
Eugene OR 97402
Tel. 800.333.9826

MIDWEST DIVISION

1549 Hwy 2
Two Harbors MN 55616
Tel. 218 834 3922

SOUTHERN DIVISION

100 Dixie Mae Drive
Pineville LA 71361
Tel. 800 444 9826

EPlly-Sealer (A) Cherry #2501430

Sealer for Engineered Wood

DESCRIPTION

The Willamette Valley Company has formulated EPlly-Sealer (A) Cherry, a high quality face sealer specifically designed to meet the needs of the plywood and engineered wood industries. It is a surface treatment that minimizes checking, splitting and moisture damage which cause the dimensional instability of wood substrates. EPlly-Sealer (A) has excellent water repellency and less stickiness than regular paraffin wax-based sealers. It is an economical and environmentally safe product.

WHERE TO USE

- Engineered Wood Products: LVL, OSB
- Plywood Plants
- Other Wood Product Plants

FEATURES AND BENEFITS

- Excellent Water Repellency and Moisture Protection
- Ease of Application
- Environmentally Sound
- Long Lasting Moisture Barrier

PACKAGING

1-Gallon (3.78 L) Pails
5-Gallon (18.93 L) Pails
Drums
Totes
Tankers

SHELF LIFE

3 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment above 45°F (7.2°C). DO NOT FREEZE.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

pH (varies dependent on color)	9.1
Viscosity at 78°F (25.5°C) (centipoise)	248
Solids (percent by weight)	29%
Wt. / Gal. lbs/gallon (kg/liter)	8.25 (0.99)
Color – Cherry	

APPLICATION

Apply one coat of EPlly-Sealer (A) by HVLP, airless spray or flood coater at a film thickness of 3-5 mils. If a higher application rate is applied to obtain a higher performance, a blocking concern needs to be considered. EPlly-Sealer (A) can be recoated with a suitable glue system for flooring applications. Check with your Willamette Valley Company representative for directions and recommendations.

CLEAN-UP

EPlly-Sealer (A) can be washed off with water prior to the film drying. If the sealer has dried, scrubbing with hot water and detergent is advised.

NOTES

This product is supplied to the customer in a ready to use form. Any addition of water will result in degradation of the product performance.

HEALTH AND SAFETY

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

CONTACT INFORMATION

Please see the side bar on the right and the front page for the Division nearest to your location.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com
info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

1075 Arrowsmith Street
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQUIK.com
www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SUBSIDIARIES

CANADIAN WILLAMETTE

19081- 27th Avenue
Surrey BC V3S 5T1
Tel. 800.663.4298

ECLECTIC PRODUCTS INC.

Corporate Office
1075 Arrowsmith Street
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
Po Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625 Parque
Industrial Coronel Coronel, Chile
Tel 011.56.41.928.100
www.tapel.cl



Revision Date: August 2013

DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.