

# Technical Data Sheet



**W V C O**

Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,  
innovation, and integrity

#### WESTERN DIVISION

660 McKinley Street

Eugene OR 97402

Tel. 800.333.9826

#### EASTERN DIVISION

6662 Marbut Road

Lithonia GA 30058

Tel. 888.878.9826

#### CANADIAN WILLAMETTE

19081- 27th Avenue

Surrey BC V3S 5T1

Tel. 800.663.4298

#### SOUTHERN DIVISION

100 Dixie Mae Drive

Pineville LA 71361

Tel. 800 444 9826

# OSB STENCIL/STRIPING PAINT Pink

## Paint for Stenciling on Oriented Strand Board

### DESCRIPTION

OSB Stencil Paint Pink is designed for stenciling company logos and other markings needed on OSB. The wax-based paint creates crisp pink lettering, striping and numbers on Oriented Strand Board.

### WHERE TO USE

- OSB Plants

### FEATURES AND BENEFITS

- Easy to See Crisp Pink Color
- Use with Airless Spray Equipment
- Ready-to-Use

### PACKAGING

5 – gallon (18.93 L) pails  
Drums  
Totes

### SHELF LIFE

6 months when properly stored.

### STORAGE

Store this product in a clean, dry, shaded or covered environment out of direct sun light.

DO NOT FREEZE – Store between 38-100°F (3.3-37.8°C)

## TECHNICAL INFORMATION

### TYPICAL PROPERTIES

Viscosity, cps	1000
Weight lb / gal (Kg/L)	10.5 (1.26)
Percent Solids	41%
pH	9.0
Color	Pink

## APPLICATION

Apply OSB Stencil Paint Pink by airless spray at a recommended film thickness of 4-8 wet mils. Check with your Willamette Valley Company representative for directions and recommendations for use with other types of application methods.

This product is supplied to the customer in a ready-to-use form. Any addition of water or other substances will result in degradation of the product performance.

---

### CLEAN-UP

---

OSB Stencil Paint can be washed off with water prior to the film drying. If the sealer has dried, scrubbing with warm soapy water is advised.

---

### CONTACT INFORMATION

---

Please see the side bar on the front page for the Division nearest to your location.

---

### HEALTH AND SAFETY

---

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800-333-9826 or send an email to: [msds@wilvaco.com](mailto:msds@wilvaco.com).

#### **WILLAMETTE VALLEY COMPANY**

[www.wilvaco.com](http://www.wilvaco.com)  
[info@wilvaco.com](mailto:info@wilvaco.com)

#### **OTHER DIVISIONS**

##### **PERFORMANCE COATINGS**

1075 Arrowsmith Street  
PO Box 2280  
Eugene, OR 97402  
Tel 541.484.9621  
[www.POLYQuik.com](http://www.POLYQuik.com)  
[www.wvcorailroad.com](http://www.wvcorailroad.com)

##### **PRECISION TECHNOLOGIES DIVISION**

675 McKinley Street  
Eugene, OR 97402  
Tel 541.484.2368  
[www.pre-tec.com](http://www.pre-tec.com)

#### **SUBSIDIARIES**

##### **ECLECTIC PRODUCTS INC.**

Corporate Office  
1075 Arrowsmith Street  
Eugene, OR 97402  
Tel 541.284.4667  
[www.eclecticproducts.com](http://www.eclecticproducts.com)

##### **IDAHO MILL & GRAIN**

445 North 430 West Hwy  
Po Box 188  
Malad City, Idaho 83252  
Tel 208.766.2206

##### **TAPEL WILLAMETTE LTD. S.A.**

Av. Estero La Posada 3625  
Parque Industrial Coronel  
Coronel, Chile  
Tel 011.56.41.2928.100  
[www.tapel.cl](http://www.tapel.cl)

---

#### **DISCLAIMER OF WARRANTY**

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.

