

Technical Data Sheet



Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through
service, innovation, and
integrity

WESTERN DIVISION

660 McKinley Street
Eugene OR 97402
Tel. 800.333.9826

EASTERN DIVISION

6662 Marbut Road
Lithonia GA 30058
Tel. 888.878.9826

CANADIAN DIVISION SURREY BRANCH

19081- 27th Avenue
Surrey BC V3S 5T1
Tel. 800.663.4298

SOUTHERN DIVISION

100 Dixie Mae Drive
Pineville LA 71361
Tel. 800 444 9826

OSB STENCIL/STRIPING PAINT HD

Paint for Oriented Strand Board

DESCRIPTION

OSB Stencil/Striping Paint HD is designed for stenciling company logos and other markings needed on OSB. The wax-based paint creates crisp lettering, striping and numbers on Oriented Strand Board.

WHERE TO USE

- OSB Plants

FEATURES AND BENEFITS

- Vibrant Colors
- Used with Airless Spray Equipment
- Ready to Use

PACKAGING

5-gallon (18.93 L) pails
Drums
Totes

SHELF LIFE

6 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment out of direct sun light.
DO NOT FREEZE – Store between 38-100°F (3.3-37.8°C)

TECHNICAL INFORMATION

TYPICAL PROPERTIES

Viscosity, cps # 3 @50 RPM	800
Weight lb / gal (Kg/L)	10.55 (1.267)
Percent Solids	47%
pH	9.5
Color	White and custom colors

APPLICATION

Apply OSB Stencil/Striping Paint HD by airless spray at a recommended film thickness of 4-8 wet mils. Check with your Willamette Valley Company representative for directions and recommendations for use with other types of application methods.

This product is supplied to the customer in a ready-to-use form. Any addition of water or other substances will result in degradation of the product performance.

CLEAN-UP

OSB Stencil/Striping Paint HD can be washed off with water prior to the film drying. If the sealer has dried, scrubbing with warm soapy water is advised.

CONTACT INFORMATION

Please see the side bar on the front page for the Division nearest to your location.

HEALTH AND SAFETY

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com
info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

1075 Arrowsmith Street
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQuik.com
www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SUBSIDIARIES

ECLECTIC PRODUCTS INC.

Corporate Office
1075 Arrowsmith Street
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
PO Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625
Parque Industrial Coronel
Coronel, Chile
Tel 011.56.41.2928.100
www.tapel.cl



DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.

W07-R&D-TDS-049

REV00

Revision: July 2016