

Technical Data Sheet



Willamette Valley Company

www.wilvaco.com

www.polyquik.com

800.333.9826

Partnering through service,
innovation, and integrity

POLYQuik® EJC-25

Expansion Joint Compound with 25% movement capability

DESCRIPTION

POLYQuik® EJC-25 is a rapid setting, 2-component, self-leveling joint sealant with excellent adhesion and durability. EJC-25 has demonstrated superior long-term performance for joint sealant applications with small to moderate movement requirements.

WHERE TO USE

- Airports
- Bridge Joints
- Highways
- Parking Decks
- Sidewalks
- Any Joint with $\pm 25\%$ Movement

FEATURES AND BENEFITS

- **Rapid Cure**— as little as 1 hour return to service
- **Self-Leveling**—flows easily, completely fills joint
- **Flexible at Freezing Temperatures**
- **ASTM C920**—Type M, Grade P, Class 25
- **100% Solids, 0 VOC**—environmentally friendly
- **1:1 Ratio by Volume**—easy application

PACKAGING

20-oz. (600 mL) Cartridge
50-oz. (1500 mL) Cartridge
5-Gallon (19 Liter) Pail
50-Gallon (190 Liter) Drum

COLORS

Black, Gray

SHELF LIFE

1 year when properly stored.

STORAGE

Store and ship this product in clean, dry, low-humidity, and shaded or covered environments between 50 and 90°F (10-32°C)

TYPICAL PROPERTIES

	Result	ASTM
Solids Content	100%, SCAQMD compliant	D2369
Cyclic Movement Capabilities, Class 25	Passes 10 cycles, no loss of adhesion or cohesion	C719, C920 (4.1.5)
Tack-Free Time	45 minutes	C679
Concrete Adhesion, primed with POLYQuik® PolyPrime	≥ 50 pli (8.8 N/mm)	C794
Concrete Adhesion, unprimed	10 pli (1.8 N/mm)	C794
FastPatch Adhesion, unprimed	≥ 40 pli (7.0 N/mm)	C794
Hardness	45-55 Shore A	C661
Mix Ratio (by Volume)	1:1	-

APPLICATION INSTRUCTIONS

For instructions on how to handle and apply POLYQuik® EJC-25 from cartridges, please refer to [POLYQuik® Cartridge Instructions](#).

For instructions on how to apply POLYQuik® EJC-25 from bulk containers with WVCO/Pre-Tec meters, training will be provided. If you have specific questions related to your dispensing equipment, please contact your WVCO representative or customer support.

For joint design and installation instructions, please refer to: [POLYQuik® Joint Design and Installation Guidelines](#)

ESTIMATED COVERAGE

Coverage chart assumes appropriate backer rod placement to provide 1/8 inch (3 mm) recessed sealant fill and 1/2 inch (13mm) sealant depth for the entire joint length.

Joint Width	Linear feet (meter) coverage per 20 oz (600mL) cartridge	Linear feet (meter) coverage per gallon (3.8 Liter)
0.5 in (13 mm)	10 (3.0)	64 (19.5)
1.0 in (25 mm)	5.5 (1.7)	35 (10.7)
1.5 in (38 mm)	3.75 (1.1)	24 (7.3)
2.0 in (51 mm)	2.9 (0.9)	18.3 (5.6)

HEALTH AND SAFETY

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS, please call 800-333-9826 or send an email to: msds@wilvaco.com

DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. PROPER APPLICATION IS THE RESPONSIBILITY OF THE USER. AS WITH ANY PRODUCT THE USE OF THIS PRODUCT IN A GIVEN APPLICATION MUST BE TESTED (INCLUDING BUT NOT LIMITED TO FIELD TESTING) IN ADVANCE BY THE USER TO DETERMINE SUITABILITY. TESTING IS THE REQUIREMENT OF BOTH ENGINEERS AND CONTRACTORS ALIKE. WVCO DOES NOT WARRANT THE APPLICATION UNDER ANY OR ALL CIRCUMSTANCES.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com
info@wilvaco.com

DIVISIONS

WESTERN DIVISION

1075 Arrowsmith Street
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQUIK.com
www.SPIKEFAST.com

EASTERN DIVISION

6662 Marbut Road
Lithonia, GA 30058
Tel 888.878.9826

MIDWEST DIVISION

1549 Hwy 2
Two Harbors, MN 55616
Tel 218.834.3922

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SOUTHERN DIVISION

100 Dixie Mae Drive
PO Box 4450
Pineville, Louisiana 71361
Tel 318.640.5077

SUBSIDIARIES

CANADIAN WILLAMETTE

19081- 27th Avenue
Surrey BC V3S 5T1
Tel. 800.663.4298

ECLECTIC PRODUCTS INC.

Corporate Office
1075 Arrowsmith Street
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
PO Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625
Parque Industrial Coronel
Coronel, Chile
Tel 011.56.41.2.928.100
www.tapel.cl



Revision Date: December 2014