

# Technical Data Sheet



**W V C O**

Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,  
innovation, and integrity

## CANADIAN DIVISION

Surrey Branch  
19081- 27 Avenue  
Surrey BC V3Z 5T1  
Tel. 800.663.4298

## WESTERN DIVISION

660 McKinley Street  
Eugene OR 97402  
Tel. 800.333.9826

## EASTERN DIVISION

6662 Marbut Road  
Lithonia GA 30058  
Tel. 888.878.9826

## MIDWEST DIVISION

1549 Hwy 2  
Two Harbors MN 55616  
Tel. 218 834 3922

## SOUTHERN DIVISION

100 Dixie Mae Drive  
Pineville LA 71361  
Tel. 800 444 9826

# Ultra Form

## Concrete Form Board Edge Paint

### DESCRIPTION

Willamette Valley Company has formulated Ultra Form as a waterborne paint specifically designed to meet the needs of plywood mills that manufacture plywood used to make forms for concrete. The coating helps maintain the integrity of the boards edge when used under the conditions of forming concrete. Ultra Form can be manufactured in any color and it can be sprayed with many conventional paint spraying systems.

### WHERE TO USE

- Industrial Manufacturer of Concrete Form Boards
- Concrete Contractors Recoating Form Boards

### FEATURES AND BENEFITS

- Excellent Moisture Protection
- Increases Form Board Useful Life
- Vibrant Colors Attract Customers
- Available in a Variety of Colors
- Helps Prevent Checking

### PACKAGING

5-gallon pails  
Drums  
Totes

### SHELF LIFE

6 to 9 months when properly stored.

### STORAGE

Store this product in a clean, dry, shaded or covered environment above 45°F (7.2°C). DO NOT FREEZE.

## TECHNICAL INFORMATION

### TYPICAL PROPERTIES

Percent Solids	45%
Viscosity, cps, ASTM D 4878	4850
Wt/gal. (Kg/ L)	9.19 (1.1)
Coverage, sq. ft. / U.S. gal. (sq. meters / L)	325 (8)
Color	Available in many colors

### APPLICATION

Apply one coat of Ultra Form, as supplied by airless spray, brush or rolling at a wet film thickness of 4-6 wet mils. For porous wood or higher performance, increased film thickness is advised. For other types of application methods check with your Willamette Valley Company representative for directions and recommendation for use. Stenciling and any recoating should be done before the paint has dried completely and formed an impervious film.

### CLEAN-UP

Clean equipment before paint dries completely. If the paint has dried, hot water, detergent and scrubbing will be required.

### NOTES

This product is supplied to the customer in a ready to use form. Any addition of water to reduce viscosity may result in degradation of the product performance.

---

### HEALTH AND SAFETY

---

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: [msds@wilvaco.com](mailto:msds@wilvaco.com).

---

### CONTACT INFORMATION

---

Please see the side bar on the front page for the Division nearest to your location.

#### **WILLAMETTE VALLEY COMPANY**

[www.wilvaco.com](http://www.wilvaco.com)  
[info@wilvaco.com](mailto:info@wilvaco.com)

#### **OTHER DIVISIONS**

##### **PERFORMANCE COATINGS**

1075 Arrowsmith Street  
PO Box 2280  
Eugene, OR 97402  
Tel 541.484.9621  
[www.polyquik.com](http://www.polyquik.com)  
[www.wvcorailroad.com](http://www.wvcorailroad.com)

##### **PRECISION TECHNOLOGIES DIVISION**

675 McKinley Street  
Eugene, OR 97402  
Tel 541.484.2368  
[www.pre-tec.com](http://www.pre-tec.com)

#### **SUBSIDIARIES**

##### **ECLECTIC PRODUCTS INC.**

Corporate Office  
1075 Arrowsmith Street  
Eugene, OR 97402  
Tel 541.284.4667  
[www.eclecticproducts.com](http://www.eclecticproducts.com)

##### **IDAHO MILL & GRAIN**

445 North 430 West Hwy  
Po Box 188  
Malad City, Idaho 83252  
Tel 208.766.2206

##### **TAPEL WILLAMETTE LTD. S.A.**

Av. Estero La Posada 3625  
Parque Industrial Coronel  
Coronel, Chile  
Tel 011.56.41.2 928.100  
[www.tapel.cl](http://www.tapel.cl)

---

#### **DISCLAIMER OF WARRANTY**

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.

