

Technical Data Sheet



W V C O

Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,
innovation, and integrity

WESTERN DIVISION

660 McKinley Street
Eugene OR 97402
Tel. 800.333.9826

EASTERN DIVISION

6662 Marbut Road
Lithonia GA 30058
Tel. 888.878.9826

MIDWEST DIVISION

1549 Hwy 2
Two Harbors MN 55616
Tel. 218 834 3922

SOUTHERN DIVISION

100 Dixie Mae Drive
Pineville LA 71361
Tel. 800 444 9826

WB Putty 274

Water-based Filler for Panels

DESCRIPTION

Willamette Valley Company's WB Putty 274 is a water-based acrylic wood filler used to repair defects in all types of plywood panels. This putty is formulated to be smoothly applied with a flexible putty knife. Once dried it can be easily sanded, stained or painted.

WHERE TO USE

- Woodworking Shops
- Industrial Mill Environments

FEATURES AND BENEFITS

- Smooth Application
- Fast Drying
- No Cracking
- Negligible Shrinkage
- Reduced Blocking
- Easy Sanding with Little Pull-Out

PACKAGING

Drums
Totes

SHELF LIFE

8 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment. DO NOT FREEZE.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

Percent Solids by Weight	73
Viscosity, cps, ASTM D 4878	260,000
Weight / Gallon Kilograms/liter	6.62 0.8
Color	Woodtones

DRY TIME

A thin film will dry in minutes. Thicker applications may require hours to dry. Dry time depends on temperature, humidity and thickness of film.

CLEAN-UP

WB Putty 274 can be washed with water prior to drying. If it has dried, steam or mechanical abrasion is recommended.

NOTES

This product is supplied to the customer in a ready to use form. Any additions may result in degradation of the product performance.

CONTACT INFORMATION

Please see the side bar for the Division nearest to your location.

APPLICATION

This product is formulated to be applied in woodworking shops and industrial mill applications with a flexible blade putty knife. For other methods of application, check with your Willamette Valley Company Representative.

HEALTH AND SAFETY

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800 333 9826 or send an email to: msds@wilvaco.com.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com
info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

1075 Arrowsmith Street
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQuik.com
www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SUBSIDIARIES

CANADIAN WILLAMETTE

19081- 27th Avenue
Surrey BC V3S 5T1
Tel. 800.663.4298

ECLECTIC PRODUCTS INC.

Corporate Office
1075 Arrowsmith Street
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
Po Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625
Parque Industrial Coronel
Coronel, Chile
Tel 011.56.41.2928.100
www.tapel.cl

DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.



Revision Date: March 2013